



DDSCBL/ADM/2026-27/317

Date:17.06.2026

NOTICE FOR INVITING QUOTATIONS

Subject: Invitation of Quotations for Repair and Maintenance Work of Head Office Building & Nani Daman Branch

Sealed quotations are hereby invited from eligible and experienced contractors for carrying out the below-mentioned repair and maintenance work:

Name of Work:

Repairs and Maintenance Works at The Daman & Diu State Co-operative Bank Ltd., Head Office & Nani Daman Branch

The quotation shall be submitted strictly as per the Abstract Sheet enclosed.

Schedule:

- **Last Date for Submission of Quotation:** 23.06.2026 up to 5:00 PM

Submission Details:

- Quotations shall be submitted in a sealed envelope superscribing "Quotation for Repair & Maintenance Work – HO & Nani Daman Branch".
- The quotation should be addressed to:
The General Manager (ADM)
The Daman & Diu State Co-operative Bank Ltd., Head Office

Terms & Conditions:

1. The contractor should have prior experience in similar civil repair and waterproofing works.
2. The Bank reserves the right to accept or reject any or all quotations without assigning any reason thereof.
3. Payment shall be released based on actual work executed and duly certified by the Bank/Engineer.
4. The contractor shall use standard quality materials as per specifications and as approved by the Bank.
5. The work shall be completed within the stipulated time period as decided by the Bank.

A. Balaji



The General Manager (ADM)
The Daman & Diu State Co-operative Bank Ltd.

ABSTRACT SHEET

Name of Work :-Repairs and Maintenance woks at The Daman & Diu state co-op bank ltd, Nani Daman branch.

Sr. No.	Description	Unit	Estimate Qty.	Rate	Amount
01-	Dismantling plaster of thickness 20mm laid in mortar including stacking of serviceable materilas and disposal of unserviceable materials with all lead and lift	m ²	144.00		
02-	Scraping of terrace including stacking of serviceable materilas and disposal of unserviceable materials with all lead and lift. Brick bat covering	m ²	26.25		
03-	Providing Material, Labour and equipments for Providing and laying integral cement based water proofing treatment including preparation of surface as required for treatment of roofs, balconies, terraces etc consisting of following operations: a) Applying a slurry coat of neat cement using 2.75 kg/sqm of cement admixed with water proofing compound conforming to IS. 2645 and approved by Engineer-in-charge over the RCC slab including adjoining walls upto 300 mm height including cleaning the surface before treatment. b) Laying brick bats with mortar using broken bricks/brick bats 25 mm to 115 mm size with 50% of cement mortar 1:5 (1 cement : 5 coarse sand) admixed with water proofing compound conforming to IS : 2645 and approved by Engineer-in-charge over 20 mm thick layer of cement mortar of mix 1:5 (1 cement :5 coarse sand) admixed with water proofing compound conforming to IS : 2645 and approved by Engineer-in-charge to required slope and treating similarly the adjoining walls upto 300 mm height including rounding of junctions of walls and slabs.c) After two days of proper curing applying a second coat of cement slurry using 2.75 kg/ sqm of cement admixed with water proofing compound conforming to IS : 2645 and approved by Engineer-in-charge. d) Finishing the surface with 20 mm thickjointless cement mortar of mix 1:4 (1 cement :4 coarse sand) admixed with water proofing compound conforming to IS : 2645 and approved by Engineer-in-charge including laying glass fibre cloth of approved quality in top layer of plaster and finally finishing the surface with trowel with neat cement slurry and making pattern of 300x300 mm square 3 mm deep. e) The whole terrace so finished shall be flooded with water for a minimum period of two weeks for curing and for final test. All above operations to be done in order and as directed and specified by the Engineer-in-Charge : including Khurra & Gola work With average thickness of 120 mm and minimum thickness at khurra as 65 mm, etc complete as directed by engineer-incharge.	m ²	235.00		
04-	20mm thick sand faced cement plaster on walls upto height 10 metres above ground level consisting of 12mm thick backing coat of C.M. 1:3 (1-cement : 3-sand) and 8mm thick finishing coat along mixer of reliance recron 3S in proportion 1 packet for 1 bags cement mortar etc. complete as directed by the Engineer in charge.	m ²	180.00		

05-	Applying two coats of Smart care Damp Proof fiber-reinforced elastomeric waterproofing membrane designed to protect exterior vertical walls and terraces of asian Paints or equivalent make. after preparing the surface by cleaning the surface with a wire brush or high-speed water jet to remove all dust, grease, and loose particles. and applying 1 coat of crack filling material using white cement and Dr. fixit mixed with water in 3:1 ratio. further making the surface smooth finished all complete as directed by the Engineer in charge.	m ²	875.00		
06-	Finishing wall with two coats of Smart care Damp Proof fiber-reinforced elastomeric waterproofing membrane designed to protect exterior vertical walls and terraces of asian Paints or equivalent make to give an required shape even shade after thoroughly brushing the surface to remove all dirt, and remains of loose powdered materials.etc complete	m ²	1188.00		
				Total Rs.	
				Add 18% GST	
				Total	
				Say Rs.	